How to change serpentine belt on **Audi A3 8PA** – replacement guide

VIDEO TUTORIAL



Important!

This replacement procedure can be used for:
AUDI A1 Sportback (8XA, 8XK) 1.2 TFSI, AUDI A3 Hatchback (8P1) 1.2 TSI, AUDI A3 Sportback (8PA) 1.2 TSI, AUDI A1 Hatchback (8X1, 8XK) 1.2 TFSI, AUDI A3 Convertible (8P7) 1.2 TFSI

The steps may slightly vary depending on the car design.

REPLACEMENT: SERPENTINE BELT – AUDI A3 8PA.
TOOLS YOU'LL NEED:



- Combination spanner #16

BUY TOOLS

Replacement: serpentine belt – Audi A3 8PA. Tip from AUTODOC experts:


- All work should be done with the engine stopped.

REPLACEMENT: SERPENTINE BELT – AUDI A3 8PA. RECOMMENDED SEQUENCE OF STEPS:

1 Lift the car using a jack or place it over an inspection pit.




2 Pull aside the V-ribbed belt tensioner pulley. Use a combination spanner #16.



3 Remove the V-ribbed belt.




4 Return the tensioner pulley to its initial position.



Replacement: serpentine belt – Audi A3 8PA. Tip:

- Check the condition of the tensioner pulley and idler pulley. Replace them if necessary.


5 Install the V-ribbed belt.



Replacement: serpentine belt – Audi A3 8PA. AUTODOC recommends:

- Make sure that the V-ribbed belt fits all pulleys snugly.

6 Pull aside the V-ribbed belt tensioner pulley. Use a combination spanner #16.



7 Place the V-ribbed belt on the tensioner pulley.



8 Return the tensioner pulley to its initial position. Use a combination spanner #16.



9 Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.

10 Shut off the engine.

11 Lower the car.



WELL DONE!

VIEW MORE TUTORIALS

AUTODOC — TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR AUDI

SERPENTINE BELT: A WIDE SELECTION

ⓘ DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.